



**UNIQUE HEATED  
PRODUCTS**

**Get your quote today!  
586-783-5725**

## **HEATED AND INSULATED BLANKETS**

**Unique Heated Products' Heated and Insulated Blankets** are designed for viscosity control, freeze protection, and dispensing temperature sensitive media. **UHPI's** use of superior insulations and a completely uniform, proprietary heating element applied to the blanket's entire inner surface creates the most temperature stable heated blanket on the market.

Meet tomorrow's regulations today - CALL **UNIQUE**



### **FEATURES AND SPECIFICATIONS**

**Wrap-around Blankets** protect cylindrical or cubical shapes and typically use Velcro™, zippers, or laced grommets to hold them in place. Custom designed to heat in situ pipes, hoses, valves, and other components, these blankets are ideal when pumping temperature-critical substances.



- Temperatures up to 400° C with 600° C internal exposure capability
- Can be used outdoors
- Blanket material and insulation to be determined by **UHPI**
- Can be designed for all applications



**UNIQUE HEATED  
PRODUCTS**

22797 Macomb Industrial Dr.  
Clinton Twp. MI 48036

**Toll Free 800-628-8239**

**or Local 586-783-5725**

**[www.heatedproducts.com](http://www.heatedproducts.com)**



**UNIQUE HEATED PRODUCTS**

**Get your quote today!  
586-783-5725**

## HEATED AND INSULATED BLANKETS ORDERING GUIDE

EXAMPLE: BKT-D-2-120-10-G-B-C-5-A-AK-D72-000

FIELD NUMBER:            1   2   3   4   5   6   7   8   9   10   11   12

**1. INSIDE MATERIAL**

TO BE DETERMINED BY UHP

**2. OUTSIDE MATERIAL**

TO BE DETERMINED BY UHP

**3. LENGTH IN INCHES**

OVERALL LENGTH

**4. WIDTH IN INCHES**

OVERALL WIDTH

**5. INSULATION TYPE**

TO BE DETERMINED BY UHP

**6. TEMPERATURE RANGE**

- A-100° C (212° F)
- B-200° C (392° F)
- C-300° C (572° F)
- D-400° C (752° F)

**7. INTERNAL EXPOSURE RANGE**

- A-100° C (212° F)
- B-200° C (392° F) (MOST COMMON)
- C-300° C (572° F)
- D-400° C (752° F)
- E-500° C (932° F)
- F-600° C (1082° F)

**8. CLOSURE TYPE**

- 1-HOOK AND LOOP (VELCRO)
- 2-GROMMET
- 3-HOOK AND EYE
- 4-NONE (FLAT BLANKET)
- 5-ZIPPER
- 7-RINGLET AND LACE

**9. HEATER VOLTAGE**

- A-120 VAC
- B-230 VAC
- G-12 VDC
- H-208 VAC
- I-240 VAC

**10. SENSOR TYPE**

- A-THERMOCOUPLE (J OR K)
- B-THERMISTOR
- C-RTD (PT100)
- D-ADJUSTABLE T-STAT
- E-SELF-LIMITING

**11. POWER CABLE TYPE (LENGTH)**

- A-7 PIN CONNECTOR (13 AMP MAX)
- B-7 PIN CONNECTOR (45 AMP MAX)
- E-SO CORD W/NEMA 5-15 PLUG
- F-FLEXIBLE CONDUIT
- G-MILSPEC CONNECTOR
- H-CLASS 1 DIVISION 2
- I-CLASS 1 DIVISION 1
- J-3 PIN MOLEX CON. (11 AMP MAX)
- K-SO CORD W/NEMA 6-30 PLUG
- M-MALE TWIST LOCK W/TC
- N-9 PIN CONNECTOR (13 AMP MAX)
- R-CONNECTOR BOX W/7 PIN CON.

**12. OPTIONS**

FOR ALL OPTIONS PLEASE SEE  
OPTION PAGE OR CONTACT  
UHP SALES AND TECH SUPPORT



**UNIQUE HEATED PRODUCTS**

22797 Macomb Industrial Dr.  
Clinton Twp. MI 48036